

# SURVEY RECOVERY FORM

City of Everett  
Department of Public Works

State of Washington  
County: Snohomish

Station Name: 728 44 02

Horizontal Datum: NAD 83/91

Vertical Datum: NAVD 88

Control Point ID: Book: 728

Page: 44

Pt#: 02

Established By: Perteet Eng.

Date: 4/29/2003

Edited by Geodetic Consultants 06/03/2002

Section: 36

Township: 29 N

Range: 04 E

LATTITUDE: (5 decimal places) 47 57 20.98174

LONGITUDE: (5 decimal places) 122 14 03.11868

ORTHOMETRIC HEIGHT: \_\_\_\_\_ Feet  
\_\_\_\_\_ Meters

## Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	351780.852	1297182.614	0.999946239	-01 02 34.7
Meters	107223.0181	395382.0515		

### HORIZONTAL DATA:

Horizontal position established by:

\_\_\_\_\_ resection survey, comments

☒ GPS survey, GPS adjustment software used: Leica Series 500/Pro

\_\_\_\_\_ other, explain: \_\_\_\_\_

surveyor's estimated relative positional accuracy: \_\_\_\_\_ ft. @ \_\_\_\_\_ 95% confidence

surveyor's estimated absolute positional accuracy: \_\_\_\_\_ ft. @ \_\_\_\_\_ % confidence

### VERTICAL DATA:

Vertical position established by:

\_\_\_\_\_ differential leveling to: \_\_\_\_\_ order accuracy

\_\_\_\_\_ GPS survey, accuracy within \_\_\_\_\_ ft \_\_\_\_\_ meters

surveyor's estimated relative positional accuracy: \_\_\_\_\_ ft @ \_\_\_\_\_ 95% confidence

surveyor's estimated absolute positional accuracy: \_\_\_\_\_ ft @ \_\_\_\_\_ % confidence

### MONUMENT DESCRIPTION

A 2 inch brass tack with a punch mark set in a 4x4 inch concrete block, 0.55 ft under an iron monument case and cover

### TO REACH

Located on the centerline of 5<sup>th</sup> Avenue West 133 feet south of the intersection of Wood Place and 5<sup>th</sup> Avenue West.

### REFERENCES

Az from North	Distance	Reference Description
---------------	----------	-----------------------

Month & Year Recovered:

Condition of Mark:

Recovered By: